

2RB3 3AC



G-Series

Selection and ordering data for side channel blowers in vacuum and pressure operation.

	HZ	KW	V	A	kg	dB(A)	m ³ /h	mbar	mbar	
• 2RB 310-7AH06	50	0.55	200-240 △ /345-415	2.8 △ /1.6Y	11	55	100	-110	120	1×2B×2110/...2141
	60	0.63	220-275 △ /380-480	3.0 △ /1.7Y		57	120	-110	120	1×2B×2114/...2142
• 2RB 310-7AH16	50	0.75	200-240 △ /345-415	3.8 △ /2.2Y	12	55	100	-150	150	1×2B×2110/...2141
	60	0.83	220-275 △ /380-480	3.8 △ /2.2Y		57	120	-150	140	1×2B×2114/...2142
• 2RB 320-7HH26	50	0.85	200-240 △ /345-415	4.2 △ /2.4Y	17	58	110	-200	230	1×2B×2110/...2141
	60	0.95	220-275 △ /380-480	4.0 △ /2.3Y		60	130	-240	240	1×2B×2114/...2142
• 2RB 320-7HH36	50	1.3	200-240 △ /345-415	5.7 △ /3.3Y	18	58	110	-280	290	1×2B×2110/...2141
	60	1.5	220-275 △ /380-480	6.0 △ /3.5Y		60	130	-300	400	1×2B×2114/...2142
• 2RB 330-7AH06	50	0.55	200-240 △ /345-415	2.8 △ /1.6Y	12	56	140	-60	60	1×2B×2110/...2141
	60	0.63	220-275 △ /380-480	3.0 △ /1.7Y		58	165	-50	50	1×2B×2114/...2142
• 2RB 330-7AH16	50	0.75	200-240 △ /345-415	3.8 △ /2.2Y	13	56	140	-100	100	1×2B×2110/...2141
	60	0.83	220-275 △ /380-480	3.8 △ /2.2Y		58	165	-115	100	1×2B×2114/...2142

Informacje techniczne i handlowe comfilter@gmail.com

2RB3 Series Selection diagram 50/60Hz 3AC



The performance curves are valid for pumping air at 15°C at the inlet flanges with an air pressure of 1.013mbar and a tolerance of ±10%. The total pressure differences are valid up to an intake and ambient temperature of 25°C .

