

2RB4 3AC



G-Series

Selection and ordering data for side channel blowers in vacuum and pressure operation.

	HZ	KW	V	A	kg	dB(A)	m ³ /h	mbar	mbar	
• 2RB 410-7AH06	50	0.7	200-240 △ /345-415	3.8 △ /2.2Y	13	63	145	-120	120	1×...2110/...2141
	60	0.83	220-275 △ /380-480	3.75 △ /2.15Y		64	175	-130	130	1×...2114/...2142
• 2RB 410-7AH16	50	0.85	200-240 △ /345-415	4.0 △ /2.3Y	16	63	145	-160	160	1×...2110/...2141
	60	0.95	220-275 △ /380-480	3.85 △ /2.25Y		64	175	-160	160	1×...2114/...2142
• 2RB 410-7AH26	50	1.3	200-240 △ /345-415	5.7 △ /3.3Y	17	63	145	-170	200	1×...2110/...2141
	60	1.5	220-275 △ /380-480	6.0 △ /3.5Y		64	175	-210	220	1×...2114/...2142
• 2RB 420-7HH36	50	1.6	200-240 △ /345-415	7.5 △ /4.3Y	25	66	150	-280	280	1×2B×2110/...2141
	60	2.05	220-275 △ /380-480	7.6 △ /4.4Y		69	180	-320	310	2×2B×2114/...2142
• 2RB 420-7HH46	50	2.2	200-240 △ /345-415	9.7 △ /5.6Y	27	66	150	-330	440	1×2B×2110/...2141
	60	2.55	220-275 △ /380-480	10.0 △ /5.8Y		69	180	-350	420	1×2B×2114/...2142
• 2RB 430-7AH06	50	0.7	200-240 △ /345-415	3.8 △ /2.2Y	14	64	180	-70	70	1×...2110/...2141
	60	0.83	220-275 △ /380-480	3.8 △ /2.2Y		65	210	-50	50	2×...2114/...2142
• 2RB 430-7AH16	50	0.85	200-240 △ /345-415	4.2 △ /2.4Y	17	64	180	-120	120	1×...2110/...2141
	60	0.95	220-275 △ /380-480	4.0 △ /2.3Y		65	210	-90	70	2×...2114/...2142
• 2RB 430-7AH26	50	1.3	200-240 △ /345-415	6.6 △ /3.8Y	18	64	180	-170	220	1×...2110/...2141
	60	1.5	220-275 △ /380-480	6.9 △ /4.0Y		65	210	-200	160	1×...2114/...2142
• 2RB 490-7AH16	50	0.6	200-240 △ /345-415	2.8 △ /1.6Y	14	63	140	-120	120	—
	60	0.85	220-275 △ /380-480	3.6 △ /2.1Y		64	175	-140	140	—

Informacje techniczne i handlowe biurostakom@gmail.com

2RB4 Series Selection diagram 50/60Hz 3AC



The performance curves are valid for pumping air at 15°C at the inlet flanges with an air pressure of 1.013mbar and a tolerance of ±10%. The total pressure differences are valid up to an intake and ambient temperature of 25°C .

